

MARK L³

Liquid Hot Water Extraction Cleaner

Limpiador Extractor En Liquido Para Agua Caliente

MARK L³ Liquid Extraction Cleaner is a highly concentrated emulsifier for use with hot water extraction or "steam" cleaning machines.

MARK L³ loosens carpet soil so that it is easily picked up by the vacuum. The soils are carried to the recovery tank of a self-contained hot water extractor or to the "dump site" of a direct hook-up machine.

MARK L³ Liquid Extraction Cleaner mixes easily with hot water. At operating temperatures above 120°F (49°C) this product will produce minimal foam.

This gentle shampoo is safe to use on all carpet fibers. It will not leave a sticky residue to mask fabric sheen and promote resoiling.

MARK L³ Extraction Cleaner cleans thoroughly and the selected optical brighteners sharpen colors to restore original beauty. **MARK-COAT** can be sprayed onto the clean carpet to reduce soiling during normal use and the need for frequent shampooing.

RECOMMENDED USES:

- Self Contained Units
- Direct Hook-Up
- Steam Machine

BENEFITS:

- Safe on all carpet fibers.
- Contains selected optical brighteners.

SPECIAL INSTRUCTIONS:

BEFORE USING ANY SPOTTER OR SHAMPOO test a small inconspicuous area for dye stability and/or fabric deterioration. Read carefully all directions and warnings on each container. For more information consult your local carpet care supplier. Do NOT over-wet carpet.

DIRECTIONS FOR USE:

FOR SELF CONTAINED UNITS: Add 2 oz. of **MARK L³** per gallon of hot water. Then add this solution to the clean water side of the extractor. The water should be above 120°F.

For additional cleaning and brightening of oxidized synthetic carpets, add 1 oz. of **MARK-BRIGHT** per gallon of mixed solution. This should be added to mixing bucket or tank prior to adding hot water. Stir thoroughly. See complete instructions on **MARK-BRIGHT** container.

FOR DIRECT HOOK-UP UNITS: **MARK L³** should be added to the machine dispenser unit as it comes from the container. Hook up machine to the hot water source and to the dump area. Turn on machine and adjust water and product flow so that after carpet is cleaned and the damp carpet has a slight slippery feel. Use approximately 2 oz. of product per 100 square feet of carpeting.