

COMPOUND 702

Triple Power Cleaner

Limpiador Con Tres Veces El Poder

This powerful alkaline liquid cleaner has been developed for use in steam cleaning, automatic scrubbing, hot tank degreasing, pressure washing, and manual cleaning. Its versatility is truly amazing. What's even more amazing is its effective removal of caked, encrusted soil and heavy oil in all these applications. This liquid is composed of strong alkalis and alkaline builders, water softeners, emulsifiers, and synthetic wetting agents.

RECOMMENDED USES:

- Pressure Washing/Steam Cleaning
- Automatic Concrete Floor Cleaning
- Engine Degreasing
- Hot Tank/Soak Tank Cleaning
- Degreasing Floors, Parts, etc.

BENEFITS:

- Versatile
- Economical/Fast Acting
- Non-flammable/Biodegradable/Solvent Free
- Effective in dissolving grease and oil
- Contains corrosion inhibitors
- Works in hot/cold water

SPECIAL INSTRUCTIONS:

- THIS PRODUCT CAN DAMAGE the following metals—aluminum, copper, brass, tin, zinc, and galvanized metal. If cleaner accidentally runs or is splashed onto these surfaces, RINSE OFF IMMEDIATELY.
- Test surface before using.

KEEP THIS AND ALL CHEMICALS OUT OF REACH OF CHILDREN

DIRECTIONS FOR USE:

Recommended for removing heavy oils, caked grease, crusted dirt, hard clay, anti-rust coatings, sludge, and other extreme conditions.

Avoid overspray onto car finish. Some paints are alkali sensitive and may be harmed. Do not use on aluminum trim or grills. At some dilutions aluminum will be etched and lose its shine.

CONCRETE CLEANING: To remove heavy oil accumulations from floors of service stations, terminal garages, airport ramps, etc. Use at dilution of 4-6 ounces to 1 gallon of water. Mop or flood area to be cleaned with solution. Let stand for 10 minutes, then agitate with stiff broom or brush. Hose off and rinse.

COMPOSITION FLOOR CLEANING: A use dilution of 4-6 ounces to 1 gallon of water is recommended for use with automatic floor machines. Usual floor cleaning procedures should be followed. Floors can be cleaned manually at same dilution. Do not allow solution to remain on the floor for prolonged periods of time.

STEAM CLEANING: To remove heavy oils, caked grease, crusted dirt and clay, anti-rust coatings, sludge, or other extreme soil conditions existing in industrial plants, shipyards, railroads, oil field operations, airports, etc. Use at a dilution of 4 ounces to 1 gallon of water. Special water conditioning agent contained in cleaner reduces possibility of scale formation.