

# eLIMEinate II

## Non Foam Acid Cleaner and Descaler *Limpiador y Quitador de Escala De Baja Espuma*

Eliminate calcium and other hard water mineral deposits with **eLIMEinate II**...a special blend of mineral acids that attacks grime and scale build-up in dish machines.

This non-foaming cleaner works effectively to descale deposits from wash arms, spray jets and interior dish machine walls. A machine cleaned with **eLIMEinate II** operates more efficiently, because water flow is unhampered by hard water build-up. **eLIMEinate II** maximizes rinse action, so dishes are **completely clean**...every time!

Regular descaling with **eLIMEinate II** also prevents dish machine breakdowns and service calls...a savings that can really impact the bottom line!

### **RECOMMENDED USES:**

- Machine Dishwashers
- Water Coolers
- Air Conditioning Coils and Filters

### **BENEFITS:**

- Removes Scale Build-Up
- Maximizes Rinse Action
- Minimizes Rejects
- Keeps Dish Machines Running At Top Efficiency
- Contains Corrosion Inhibitors

### **SPECIAL INSTRUCTIONS:**

- Follow product label directions or ask your **Daley International** Representative for specific details.

### **DIRECTIONS FOR USE:**

#### **For Quick, Safe and Easy Removal of Lime Scale, Soap Scum, Milkstone and Alkaline Food Soils**

**MACHINE DISHWASHER DESCALING:** Dump tanks and fill with clear, hot water. Turn off detergent feeder. Dilute 1:20 up to 1:64 in all tanks. Cycle machine with racks inside. Brush surfaces with built-up scale and check wash and rinse arm nozzle. Wipe outside of machine with solution in tank and wipe dry. Dump tank and rinse with clear water. Refill with detergent feeder turned on.

**STAINLESS FOOD SERVICE EQUIPMENT, ALUMINUM, PORCELAIN, CERAMIC SURFACES:** Dilute 2 to 4 ounces per gallon in hot water. Mop, brush, or spray on and rinse off. Wipe dry to shine if desired.

**RUST REMOVAL:** Dilute 4 to 6 ounces per gallon in warm water. Dip or mop on surface. Scrub with wire brush or other abrasive device. Rinse and wipe or blow dry. Treat with oil to prevent flash rust.